

INSTRUCTIONS FOR LOADING WAVEFORM FILES INTO THE BTS MASTER

The instructions should be posted and as follows:

1. On the USB memory device, create a directory called “usr” in the root directory.
2. Download all .vsg files to be loaded onto the BTS Master into the usr directory.
3. Attach the USB memory device to one of the USB ports on the BTS Master.
4. On the BTS Master, press the Shift key followed by the File (F) key. The File menu is listed.
5. Press the Directory Management submenu key. The Directory Management menu is listed.
6. Press the Current Location submenu key to select the current location of the pattern files, USB (USB memory device). The underlined location is active.
7. Press the Setup main menu key. The Setup menu is listed.
8. Press the Pattern Manager submenu key. The Custom Signal Pattern folder opens, and the Pattern Manager menu is listed.
9. Press the Add submenu. The selected folder content is listed.
10. Highlight the desired signal pattern file and press the Add Selected Pattern submenu key. The signal pattern file is added into the Custom Signal Pattern folder. The signal pattern name is displayed in a box at the bottom of the Custom Signal Pattern folder.
11. Repeat Step 6 and Step 7 to continue adding signal patterns into the Custom Signal Pattern folder.
12. Refer to chapter 3 of the [Signal Generators for Anritsu RF and Microwave Handheld Instruments Measurement Guide](#) for further vector signal generator operating instructions.