



**SSV**  
series

**SSV SERIES CHECKWEIGHERS**

- Accuracy
- Reliability
- Fully Featured
- Small Footprint

**BEST COMBINATION OF PERFORMANCE & PRICE IN A COMPACT FOOTPRINT**

Anritsu's SSV checkweighers deliver an ideal blend of accuracy and reliability in an extremely compact package. A common interface with our x-ray and metal detectors simplifies usage across Anritsu equipment.

- ▶ **Accuracy:** With accuracy as low as  $\pm 0.01g$  at  $3\sigma$  and speed up to 600 products/min, the SSV promises top performance and productivity.
- ▶ **Reliability:** With nearly 100,000 installations worldwide, Anritsu checkweighers are built to last and consistently perform.
- ▶ **Features:** Anritsu checkweighers include a broad range of standard features, including touch screen, USB, Ethernet, programmable I/O, full statistics, and auto-learn wizard.
- ▶ **Footprint:** Our checkweighers start at just 545mm (21.5 inches) long, easing installation requirements.
- ▶ **Smart Measurement Function (SMF):** Proprietary technology that minimizes false rejects from inconsistent product spacing.

Since its first checkweigher in 1964, Anritsu has grown into one of the largest providers in the world. Anritsu designs and develops its flexible weighing solutions in-house.

Anritsu's parent company, founded in 1895, is a billion-dollar global electronics giant with a legacy of innovation and meticulous engineering in telecom and testing.



Checkweighers are also available as combos, paired with Anritsu metal detectors.

**STANDARD FEATURES**

- Highest accuracy
- Small footprint
- Smart Measurement Function (SMF)
- Assured weigh compliance
- Quick setup
- Guided operation
- Easy product setup
- 200 product presets
- Reporting and auditing
- Open construction
- Tool-free belt removal
- USB and Ethernet

# MODELS & SPECIFICATIONS

✓ Available – Not Available • Standard ○ Optional

FEATURE	SSV-H	SSV-I	SSV-F
<b>DESIGN/FORMAT</b>			
Force Balance High Accuracy	•	✓	–
Strain Gauge Standard Accuracy	–	✓	•
Scale Resolutions (g)	0.001, 0.01, 0.05	0.01, 0.02, 0.05, 0.1, 0.2, 1.0	0.05, 0.1, 0.5, 1.0, 2.0
Weight Ranges (g)	100, 600, 3000	600, 1200, 3000, 15000	600, 3000, 6000, 15000, 25000
Environment	IP30	IP66	IP30
Finish	Painted - SS optional	SS	Painted - SS optional
<b>MAXIMUM ACCURACIES</b>			
@ 3 Sigma (+/- g)	0.01, 0.015, 0.1	0.1, 0.2, 0.5, 2.0	0.2, 0.5, 1.5, 2.0
<b>MAXIMUM SPEEDS</b>			
PPM	220 to 600	50 to 330	40 to 400
m/min	15 to 120	5 to 97	5 to 120
<b>WEIGHABLE PRODUCT SIZES</b>			
Length (mm)	46 to 450	60 to 600	46 to 600
Width (mm)	20 to 350	20 to 350	20 to 450
Height (mm)	5 to 450	5 to 450	5 to 600
<b>TECHNOLOGY</b>			
SMF - Smart Measurement Function for Improved OEE	•	•	•
Temperature Compensation	•	•	•
Anritsu Proprietary Weigh Cell Design	•	•	•
<b>FEATURES</b>			
Touchscreen	8.5" Standard	8.5" Standard	8.5" Standard
Removable Belting	•	•	•
Tool-Free Removable Conveyors	•	•	•
8 Additional Inputs & Output	○	○	○
Filler Feedback Filling Control	○	○	○
<b>SOFTWARE</b>			
Full Statistics - 8 Standard Display Screens	•	•	•
Product Setup Navigation	•	•	•
Multi-lingual	•	•	•
Mean Tracking & Alarm	○	○	○
Multiple/Consecutive Reject Alarm	•	•	•
QuiCCA Support	•	•	•
Operation Check (HACCP audit)	•	•	•
<b>SANITARY FEATURES</b>			
Removable Belting	Tool free	Tool free	Tool free
Tool-Free Removable Conveyor	Tool free	Tool free	Tool free
Clean Design with Easy Access	•	•	•

Subject to change, without notice

## PERFORMANCE 360

The Anritsu **P360** program provides comprehensive service, support and training, including:

- 24/7 technical support
- Preventive maintenance (quarterly site visits)
- HACCP performance (annual site visits)
- Remote support and monitoring



Anritsu Invisis, Inc.

1001 Cambridge Drive | Elk Grove Village, IL 60007-2453

+1 847-419-XRAY (9729) | [anritsu.com](http://anritsu.com)

**Anritsu**  
envision:ensure