

SLD unit with Drive Circuits **AM8P8006SL45G**

AM8P8006SL45G is 880nm SLD unit with drive circuits developed as light sources for ophthalmology OCT. It has built in both SLD light source and drive circuits so that it is suitable for embedding.


FEATURES

- Center Wavelength/ Spectral Bandwidth: 880 nm / 50 nm
- Built in SLD source and drive circuits
- SMF output
- D-sub 9pin female connector

APPLICATION

- Embedding into ophthalmology OCT
- Embedding into optical interferometry system

DIMENSIONS



ABSOLUTE MAXIMUM RATINGS

Item	Ratings	Unit
Input Voltage (+5 V _{DC})	5.5	V
Input Voltage (V _{set})	2.75	V
Storage Temperature	-20 to +65	°C
Storage Humidity	95	%

*No condensation

PIN CONFIGURATION

No.	FUNCTION	IN/OUT
1	+5 V _{DC}	IN
2	NC	—
3	SLD Enable	IN
4	Alarm	OUT
5	V _{set}	IN
6	GND	—
7	NC	—
8	NC	—
9	V _{PD}	OUT

*Alarm: Abnormal = High, Normal = Low

*SLD Enable: See Optical and electrical characteristics

OPERATING CONDITIONS

Item	Ratings	Unit
Input Voltage (+5 V _{DC})	4.75 to 5.25	V
Input Voltage (V _{set})	0 to 2.5	V
Operating Temperature	+10 to +55	°C
Operating Humidity ^{*2}	90	%

*1 No condensation

OPTICAL AND ELECTRICAL CHARACTERISTICS (T_c = 25°C)

Item	Symbol	Test condition	Min.	Typ.	Max.	Unit
Optical Output Power ^{*3}	P _{max}	V _{set} = 2.5 V	6.0	–	7.0	mW
Center Wavelength	λ _c	V _{set} = 2.5 V, -3 dB	870	880	890	nm
Spectral Bandwidth	Δλ	V _{set} = 2.5 V, -3 dB	45	50	–	nm
Supply Current	–	Output P _{max} , T _c = 55°C	–	0.4	2.0	A
Power Consumption	–	Output P _{max} , T _c = 55°C	–	2.0	10.0	W
Input Voltage (V _{set})	V _{set}	Control from P _{min} to P _{max}	0.0	–	2.5	V
V _{set} Input Impedance	–	–	5	–	–	kΩ
V _{PD} Output (Open Circuit Voltage at Output End)	V _{PD}	V _{PD} = 0 to 3 V (±0.3 V) in P _f = P _{min} to P _{max}	0.0	–	3.3	V
V _{PD} Output Impedance	–	–	–	100	–	Ω
SLD Enable Signal TTL/High	V _H	V _H : SLD ON	3.80	–	–	V
SLD Enable Signal TTL/Low	V _L	V _L : SLD OFF	–	–	1.02	V

*3 AM8P8006SL45G is designed as a component for use in customers' electronic products. As a result, it is excluded from FDA 21 CFR 1040.10 compliance. This product corresponds with IEC laser safety class 3B.

*Optical output or spectrum may be changed, due to the optical feedback.

*P_{min} : <0.1 mW, P_{max} : 6.0 to 7.0 mW



ANRITSU CORPORATION

SENSING & DEVICES COMPANY SALES DEPT.

<https://www.anritsu.com/sensing-devices>

Tel +81 46 296 6783 Fax +81 46 225 8390
5-1-1 Onna, Atsugi-shi, Kanagawa
243-8555 Japan



Contact URL

<https://www.anritsu.com/en-gb/sensing-devices/contact-us>

Please read "Notes on Handling Optical Devices" before use.

<https://www.anritsu.com/sensing-devices/guide/optdevices-handling>



■ This product and its manuals may require an Export License / Approval by the Government of the product's country of origin for re-export from your country.
Before re-exporting the product or manuals, please contact us to confirm whether they are export-controlled items or not. When you dispose of export-controlled items, the products / manuals need to be broken / shredded so as not to be unlawfully used for military purpose.

■ Anritsu Corporation reserves the right to change the content of the catalog at any time without notice.