

# CMA50

## SPECIFICATIONS

### Loss Test Sets, Light Sources, Power Meters



#### KEY FEATURES

- One button automated multi-wavelength bi-directional measurement option
- Calibrated CWDM wavelengths
- Interchangeable connectors for easy testing in different situations
- Wizard driven for simplified set-ups and use
- Selectable modes to meet any testing requirement
- Ethernet testing option
- Rugged, lightweight, cost-effective to own and use

Fast, accurate, and easy-to-use, Anritsu's CMA50 Family helps assure your loss budgets are met without burdening your operating budget. Available as light sources, power meters, and the all-in-one loss test set, the entire family is designed for simplicity, efficiency, and reliability. Based on real-life field experiences and backed by Anritsu's standard three year warranty, the CMA50 will provide years of use in a variety of applications including FTTx networks, campus LANs, long-haul telephony, and CATV distribution.

The CMA50 Family makes your measuring experience simple and error free, and includes pass or fail threshold analysis, large capacity for test results storage, and an Ethernet network testing option. In addition, when equipped with the EZ-Test option, CMA50 Loss Test Sets will automatically perform bi-directional end-to-end loss measurements at each selected wavelength, process the results, and present them on both units in just a few seconds.

Delivering the right performance, features and options, the CMA50 is the ideal tool for installation, test, and maintenance of fiber networks without the increased cost of extra features that don't provide extra benefits. Designed with your needs in mind, this lightweight, rugged family is built for the most demanding cable installation environments and will provide years of valuable service.

#### Key Benefits

- Allows testing of end-to-end PON links with a single operator.
- Up to 4 high power sources per unit out of a single port.
- EZTest one button auto bi-directional measurement option.
- Pass or fail indicators for in-field compliance.
- Rugged design provides years of use in the most challenging environments.
- Stores up to 100,000 data sets (4 MB of user data).
- Optional Visual Fault Locator (Standard on all Loss Test Set models)
- LAN Access and network testing option via RJ45 port.
- File Transfer via USB port.
- Three year standard warranty.

General Family Specifications	
Power	4 x AA Alkaline Batteries or Rechargeable NIMH battery pack, 110/220Vac Adapter
Battery Life	20 hours, typical
Auto Shut-Off	Programmable (1 to 99 minutes) or disabled
Connector Ports - Sources	Universal Latching connector with choice of adapter
Connector Ports - Meters	Universal Screw-type connector with choice of adapter
Dimensions	210 x 110 x 41 mm (8.3 x 4.3 x 1.6 in)
Weight	<910g (including batteries) depending on configuration
Operating Temperature	-10°C to +50°C (+14°F to 122°F)
Storage Temperature	-25°C to +60°C (-13°F to 140°F)
Warranty	3 years

Light Sources				
<b>Multimode</b>				
Center Wavelength <sup>1</sup>	850nm		1300nm	
Wavelength Accuracy	+/- 20nm		+30/-20nm	
Emitter Type	LED		LED	
Output Power (62.5/125 µm fiber)	-20dBm		-20dBm	
Source Linewidth (FWHM)	<50nm		<200nm	
Stability (1 hour) <sup>2</sup>	+/- 0.1dB		+/- 0.1dB	
Output Modes	CW (Continuous Wave), 270Hz, 1KHz, 2KHz Modulation			
<b>Singlemode</b>				
Center Wavelength <sup>1</sup>	1310nm	1490nm	1550nm	1625nm
Wavelength Accuracy	+/- 20nm	+/- 20nm	+/- 20nm	+/- 20nm
Emitter Type	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Output Power (G.652 fiber)	-7dBm	-7dBm	-7dBm	-7dBm
Source Linewidth (FWHM)	<5nm	<5nm	<5nm	<5nm
Stability (1 hour) <sup>2</sup>	+/- 0.05dB	+/- 0.05dB	+/- 0.05dB	+/- 0.05dB
Output Modes	CW (Continuous Wave), 270Hz, 1KHz, 2KHz Modulation			
<b>Visual Fault Locator (Standard on Loss Test Set Models, Option V for Light Source and Power Meter Models)</b>				
Center Wavelength <sup>1</sup>	650nm +/- 20nm			
Emitter Type	Laser Diode			
Output Power	1mW (0dBm) Max, 0.8mW (-1.0dBm) Typ			
Output Modes	CW (Continuous Wave), 2Hz Modulation			

Power Meters		
Model	Standard	CATV (Option C)
Wavelengths of Operation	850nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm plus CWDM wavelengths from 1270nm to 1610nm in 20nm increments	
Detector Type	InGaAs	
Measurement Range	-75dBm to +10dBm	-50dBm to +27dBm
Measurement Accuracy <sup>3,4,7</sup>	+/- 0.2dB with Pin = -65dBm to +5dBm	+/- 0.2dB with Pin = -37dBm to +27dBm
Linearity <sup>5</sup>	+/- 0.1dB	+/- 0.1dB
Maximum Input Power <sup>6,7</sup>	+10dBm	+27dBm
Modulation Detection <sup>8</sup>	270Hz, 1KHz, and 2KHz	
Wavelength Detection	Automatic recognition of calibrated wavelengths (when used in conjunction with a CMA50 light source)	
Display Resolution	0.01 (mW, µW, nW, dBr, dBm)	

Auto Bi-Direction Test Mode (Available as Option B on Loss Test Set Models only)	
Wavelengths	All Equipped Singlemode Wavelengths
Link Loss Range <sup>1</sup>	50dB (approximately 200km at 1550nm)
Link Loss Accuracy <sup>1</sup>	+/- 0.25dB excluding connector pair uncertainty
Testing Time	2.5 seconds per wavelength

Optical Return Loss (ORL) Measurements (Option O)	
Wavelengths	All Equipped Singlemode Wavelengths
ORL Range <sup>1</sup>	0 to 55dB
ORL Accuracy <sup>1</sup>	+/-0.75dB with P <sub>in</sub> = 0dB to +50dB Derates above P <sub>in</sub> =+50dB to +/-1.5dB at +55dB
ORL Stability <sup>1</sup>	+/-0.5dB at 20dB +/- 0.5dB

Options	
<b>V Option<sup>9</sup></b> Visual Fault Locator	Visible light source at 650 nm allowing to visually detect a fiber fault up to 5 km.
<b>N Option</b> Network Test	LAN access and network level continuity and frame time delay through TCP/IP protocol over its built-in 10/100 Mbps Network Interface Card.
<b>B Option</b> EZTest	Available on Loss Test Set configurations, provides one button multiple wavelength automatic bi-directional measurement. When readings are taken between two EZ Test equipped units, this feature automatically takes loss measurements at all wavelengths in each direction, and presents the combined results on both units.
<b>O Option</b> ORL with EZ Test	Optical Return Loss (ORL) option allows the measurement of optical return loss readings required for high speed transmission systems. This option automatically includes EZ Test Option B as described above.

**Notes:**

- <sup>1</sup> Typical at +23°C.
- <sup>2</sup> After 10 minute warm-up period.
- <sup>3</sup> At time of calibration. Calibration conditions: 1310nm, -10dBm, +23°C.
- <sup>4</sup> Accuracy derates below 1000nm. At 850nm, Measurement Accuracy is +/-0.35dBm with P<sub>in</sub>= -60dBm to +5dBm (or P<sub>in</sub> = -32dBm to +27dBm for CATV Option C units).
- <sup>5</sup> At +23°C, from -65dBm to +2dBm (or -37dBm to +23dBm for CATV Option C units).
- <sup>6</sup> Do not exceed maximum input power.
- <sup>7</sup> If the power meter is routinely used to measure optical signals in excess of 0dBm (+20dBm for Option C), more frequent calibration is recommended to insure measurement accuracy.
- <sup>8</sup> P<sub>in</sub> ≥ -50dBm
- <sup>9</sup> Visual Fault Locator is Standard on all Loss Test Set Models

Available Configurations										
Model Number	Multimode Sources		Singlemode Sources				Power Meter	Available Options		
	850nm	1300nm	1310nm	1490nm	1550nm	1625nm		VFL	Network	EZ Test & ORL
<b>CMA50 Light Sources</b>										
50LS35			X		X		no	yes	yes	no
50LS83	X	X					no	yes	yes	no
50LS345			X	X	X		no	yes	yes	no
50LS356			X		X	X	no	yes	yes	no
50LS3456			X	X	X	X	no	yes	yes	no
50LS8335	X	X	X		X		no	yes	yes	no
<b>CMA50 Loss Test Sets (Combined Light Source &amp; Power Meter, and includes Visual Fault Locator)</b>										
50LTS35			X		X		yes <sup>a</sup>	Std	yes	yes, B or O
50LTS83	X	X					yes <sup>a</sup>	Std	yes	yes, B or O
50LTS345			X	X	X		yes <sup>a</sup>	Std	yes	yes, B or O
50LTS356			X		X	X	yes <sup>a</sup>	Std	yes	yes, B or O
50LTS3456			X	X	X	X	yes <sup>a</sup>	Std	yes	yes, B or O
50LTS8335	X	X	X		X		yes <sup>a</sup>	Std	yes	yes, B or O
<b>CMA50 Power Meters</b>										
50PMS	no	no	no	no	no	no	Standard	yes	yes	no
50PMC	no	no	no	no	no	no	CATV	yes	yes	no

<sup>a</sup> CMA50 Loss Test Sets can be ordered with Standard or CATV (Option C) Power Meter

**Anritsu Corporation**

5-1-1 Onna, Atsugi-shi, Kanagawa, 243-8555 Japan  
Phone: +81-46-223-1111  
Fax: +81-46-296-1264

**• U.S.A.****Anritsu Company**

1155 East Collins Blvd., Suite 100, Richardson,  
TX 75081, U.S.A.  
Toll Free: 1-800-ANRITSU (267-4878)  
Phone: +1-972-644-1777  
Fax: +1-972-671-1877

**• Canada****Anritsu Electronics Ltd.**

700 Silver Seven Road, Suite 120, Kanata,  
Ontario K2V 1C3, Canada  
Phone: +1-613-591-2003  
Fax: +1-613-591-1006

**• Brazil****Anritsu Eletrônica Ltda.**

Praca Amadeu Amaral, 27 - 1 Andar  
01327-010-Paraiso-São Paulo-Brazil  
Phone: +55-11-3283-2511  
Fax: +55-11-3288-6940

**• Mexico****Anritsu Company, S.A. de C.V.**

Av. Ejército Nacional No. 579 Piso 9, Col. Granada  
11520 México, D.F., México  
Phone: +52-55-1101-2370  
Fax: +52-55-5254-3147

**• U.K.****Anritsu EMEA Ltd.**

200 Capability Green, Luton, Bedfordshire LU1 3LU, U.K.  
Phone: +44-1582-433280  
Fax: +44-1582-731303

**• France****Anritsu S.A.**

16/18 avenue du Québec-SILIC 720  
91961 COURTABOEUF CEDEX, France  
Phone: +33-1-60-92-15-50  
Fax: +33-1-64-46-10-65

**• Germany****Anritsu GmbH**

Nemetschek Haus, Konrad-Zuse-Platz 1  
81829 München, Germany  
Phone: +49 89 442308-0  
Fax: +49 89 442308-55

**• Italy****Anritsu S.p.A.**

Via Elio Vittorini, 129, 00144 Roma, Italy  
Phone: +39-6-509-9711  
Fax: +39-6-502-2425

**• Sweden****Anritsu AB**

Borgarfjordsgatan 13, 164 40 KISTA, Sweden  
Phone: +46-853470700  
Fax: +46-853470730

**• Finland****Anritsu AB**

Teknobulevardi 3-5, FI-01530 Vantaa, Finland  
Phone: +358-20-741-8100  
Fax: +358-20-741-8111

**• Denmark****Anritsu A/S**

Kirkebjerg Allé 90 DK-2605 Brøndby, Denmark  
Phone: +45-72112200  
Fax: +45-72112210

**• Spain****Anritsu EMEA Ltd.****Oficina de Representación en España**

Edificio Veganova  
Avda de la Vega, n° 1 (edf 8, pl 1, of 8)  
28108 ALCOBENDAS - Madrid, Spain  
Phone: +34-914905761  
Fax: +34-914905762

**• United Arab Emirates****Anritsu EMEA Ltd.****Dubai Liaison Office**

PO Box 500413 - Dubai Internet City  
Al Thuraya Building, Tower 1, Suit 701, 7th Floor  
Dubai, United Arab Emirates  
Phone: +971-4-3670352  
Fax: +971-4-3688460

**• Singapore****Anritsu Pte Ltd.**

60 Alexandra Terrace, #02-08, The Comtech (Lobby A)  
Singapore 118502  
Phone: +65-6282-2400  
Fax: +65-6282-2533

**• India****Anritsu Pte. Ltd.****India Branch Office**

Unit No. S-3, Second Floor, Esteem Red Cross Bhavan,  
No. 26, Race Course Road, Bangalore 560 001, India  
Phone: +91-80-32944707  
Fax: +91-80-22356648

**• P.R. China (Hong Kong)****Anritsu Company Ltd.**

Units 4&5, 28th Floor, Greenfield Tower, Concordia Plaza,  
No. 1 Science Museum Road, Tsim Sha Tsui East,  
Kowloon, Hong Kong  
Phone: +852-2301-4980  
Fax: +852-2301-3545

**• P.R. China (Beijing)****Anritsu Company Ltd.****Beijing Representative Office**

Room 1515, Beijing Fortune Building,  
No. 5, Dong-San-Huan Bei Road,  
Chao-Yang District, Beijing 10004, P.R. China  
Phone: +86-10-6590-9230  
Fax: +86-10-6590-9235

**• Korea****Anritsu Corporation, Ltd.**

8F Hyunjuk Building, 832-41, Yeoksam dong,  
Kangnam-ku, Seoul, 135-080, Korea  
Phone: +82-2-553-6603  
Fax: +82-2-553-6604

**• Australia****Anritsu Pty Ltd.**

Unit 21 / 270 Ferntree Gully Road,  
Notting Hill, Victoria 3168 Australia  
Phone: +61-3-9558-8177  
Fax: +61-3-9558-8255

**• Taiwan****Anritsu Company Inc.**

7F, No. 316, Sec. 1, Neihu Rd., Taipei 114, Taiwan  
Phone: +886-2-8751-1816  
Fax: +886-2-8751-1817