633-27



March 1, 2013

Product name: Cylindrical Nickel –Metal Hydride Battery

Reference Number TW-CE-E01-14

Material Safety data sheet for chemical products (MSDS)

1. PRODUCT AND COMPANY IDENTIFICATION

- Product name: Cylindrical Nickel-Metal Hydride Battery
- Company name: National Power Corporation
- Address: 4330 W. Belmont Ave. Chicago, Illinois, 60641, USA
- Telephone number: 1-773-686-2662
- Telefax number: 1-773-685-8316
- Emergency telephone number: 1-800-424-9300 (North America) 001-703-527-3887 (International)

2. HAZARD IDENTIFICATION

For the battery cell, chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by misuse, the gas release vent will be operated. The battery case will be breached at the extreme. Hazardous materials may be released.

Moreover, if heated strongly by the surrounding fire, acrid or harmful fumes may be emitted.

Most important hazard and effects

Human health effects:

Inhalation: The electrolyte inhalation affects the respiration tract membrane and the lungs.

Skin contact: The electrolyte skin contact affects the skin seriously and may cause dermatitis.

Eye contact: The electrolyte leaked from the battery cell is strong alkali. When it enters the eye, the cornea may be affected and it may lead to blindness.

Ingestion: the electrolyte ingestion irritates the mouth and the throat and may resulting in vomiting, nausea, hematemesis, stomach pains and diarrhea.

Environmental effects:

Since a battery cell remains in the environment, do not throw dispose into the environment.

Specific hazards:
 As previously described.

3. COMPOSITION / INFORMATION ON INGREDIENTS



Product name: Cylindrical Nickel -Metal Hydride Battery

• Substance or preparation: Preparation

Information about the chemical nature of product:

Common chemical name/	CAS number	Concentration /	Classification and hazard
General name		concentration range	labeling
Hydrogen Absorbing Alloy	7440-02-0(Ni)	20-40%	Specific hazard
	7440-48-4(Co)		
	7439-96-5(Mn)		
	7429-90-5(AI)		
Nickel-Cobalt-Zinc oxide	7440-02-0(Ni)	15-25%	Acute toxicity
	7440-48-4(Co)		Specific hazard
	7440-66-6(Zn)		
Nickel	7440-02-0	5-15%	Specific hazard
Iron	7439-89-6	20-40%	
Carbon Black	1333-86-4	0-1%	Specific hazard
Potassium Hydroxide	1310-58-3	0-15%	Acute toxicity
Sodium Hydroxide	1310-73-2		,
Lithium Hydroxide	1310-65-2		Corrosivity Irritant property

4. FIRST AID MEASURES

Internal cell materials of an opened battery cell

- Inhalation: Cover the victim in a blanket, move to place of fresh air and keep still. Seek
 medical attention immediately. When dyspnea (breathing difficulty) or asphyxia (breath-hold),
 give artificial respiration immediately.
- Skin Contact: Remove contaminated clothes and shoes immediately. Wash the adherence or contact region with soap and plenty of water. Seek medical attention immediately.
- Eye contact: Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

A battery cell and internal cell materials of an opened battery cell

Ingestion: Do not induce vomiting. Seek medical attention immediately.

5. FIRE- FIGHTING MEASURE



Product name: Cylindrical Nickel -Metal Hydride Battery

Although a battery cell is not flammable, in case of fire, move it so a safe place quickly. The following measures are taken when it cannot be moved.

- Suitable extinguishing media: Dry sand, chemical powder fire extinguishing medium.
- Specific hazards: Acrid or harmful fume is emitted during fire.
- Special protective equipment for firefighters:

Respiratory protection: protective mask

Hand protection: Protective gloves

Eye protection: Goggle or protective glasses designed to protect against liquid splashes.

Skin and body protection: protective cloth

6. ACCIDENTAL RELEASE MEASURES

Internal cell materials, such as electrolyte leaked from a battery cell, are carefully dealt with according to the following precautions.

- Personal precautions: Forbid unauthorized person to enter. Remove leaked materials with protective equipment noted in section 8.
- Environmental precautions: Do not dispose into the environment.
- Method of cleaning up: Dilute the leaked electrolyte with water and neutralize with diluted sulfuric acid. The leaked solid is moved to a container. Flush the area with water.

7. HANDLING AND STORAGE

Handling

Technical measures

Prevention of user exposure: not necessary under normal use.

Prevention of fire and explosion: Not necessary under normal use.

Precaution for safe handling: do not damage or remove the external case.

Specific safe handling advice: Never dispose in fire or expose to high temperatures. Do not soak in water or sea water. Do not expose to strong oxidizers. Do not submit to a strong mechanical shock or crush. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. When charging, use only dedicated charger or charge according to

the conditions specified.

Storage

Technical measures

Storage conditions: Avoid direct sunlight, high temperature, and high humidity. Store in a cool, dry environment (temperature: -20 ~30 degree C, humidity: from 40 to 80%).

Incompatible products: conductive materials, water, seawater, strong oxidizers and strong acids.



Product name: Cylindrical Nickel –Metal Hydride Battery
Packing material: Electrically insulated and tear proof materials are recommended.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Engineering measures: No engineering measure is necessary during normal use. In case of internal cell materials' leakage, the information below will be useful.
- Control parameters

Common chemical name/ General name	ACGIH (2011)	CGIH (2011)	
	TLV-TWA	BEI	
Nickel, Nickel compounds	(As Ni)	-	
	Metal: 1.51mg/m³		
	Soluble compounds: 0.1mg/m ³		
	Insoluble compounds: 0.2mg/m ³		
Cobalt Compounds	(As Co)	In urine: 15 micro g/l	
	0.02mg/m ³	In Blood: 1 micro g/l	
Manganese Compounds	(As Mn)	-	
	0.2mg/m ³		
Aluminum Compounds	(As Al)	-	
	1mg/m³ (Flammable powder)		
Zinc Compounds	2mg/m ³	-	
Carbon Black	3mg/m ³		
Potassium Hydroxide	-	-	
Sodium Hydroxide	_	•	
Lithium hydroxide	-	-	

ACGIH: American conference of Governmental Industrial Hygienists, Inc. TLV-TWA: Threshold Limit Value-time weighted average concentration

BEI: biological Exposure Indices

· Personal protective equipment

Respiratory protection: Protective mask

Hand protection: Waterproof protective gloves.

Eye protection: Protective glasses designed to protect against liquid splashes Skin and body protection: Working clothes with long sleeve and long trousers.



Product name: Cylindrical Nickel - Metal Hydride Battery

PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state: Solid

Form: Cylindrical and prismatic

Cell color: Metallic (without shrink tube)

Odor: No odor

- pH: NA
- Specific temperatures/temperature ranges at which changes in physical state occur.
 There is no useful information for the product as a mixture.
- Flash point: NA
- Explosion properties: NA
- Density: Around 1.5 ~ 6.0g/cm³
- Solubility, with indication of the solvent(s): insoluble in water.

10. STABILITY AND REACTIVITY

- Stability: Stable under normal use.
- Hazardous reactions occurring under specific conditions:

By misuse of a battery, oxygen or hydrogen accumulates in the cell and the internal pressure rises. These gases may be emitted through the gas release vent. When fire is near, these gases may ignite. When a battery cell is heated strongly by the surrounding fire, acrid or harmful fume may be emitted.

- Conditions to avoid: Direct sunlight, high temperature and high humidity.
- Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.
- Hazardous decomposition products: Acrid or harmful fume is emitted during fire.

11. TOXILOGICAL INFORMATION

There is no data available on the product itself. The information of the internal cell materials is as follows.

Nickel, Nickel Compounds

Acute toxicity:

Oral

GHS: out of category

Skin

Unknown

Inhalation (gas)

GHS: exempt from a classification

Inhalation (Steam)

Unknown

Inhalation (Mist)

Unknown

Controlled 150301.05



Product name: Cylindrical Nickel – Metal Hydride Battery

• Skin corrosivity: Unknown

Serious damage and irritant property for eyes: Unknown

Respiratory or skin sensitization:

Respiratory sensitization: GHS category 1

The allergy, asthma or breathing difficulties might be caused when inhaling.

Skin Sensitization: GHS: Category 1

The allergic skin reaction might be caused

· Germline mutagenicity:

GHS: it is not possible to classify it due to data deficiency.

Carcinogenicity: ACGIH: (Metal) A5 – Not suspected as a human carcinogen.

ACGIH: (Insoluble compounds) A1 - Confirmed human carcinogen.

NIOSH: Potential occupation carcinogen.

NTP: Reasonably anticipated to be human carcinogens IARC: (Metal) Group 2B possibly carcinogenic to humans.

IARC: (Compounds) Group 2B carcinogen.

Reproduction toxicity:

GHS: it is not possible to classify it due to data deficiency.

Certain target organ/ Systematic toxicity (Single exposure):

GHS: category 1 (respiratory organ and kidney).

• Certain target organ/ Systematic toxicity (repeat exposure):

GHS: category 1 (respiratory organ).

The disorder of the respiratory organ is caused by long-term or repeated exposure.

Cobalt Compounds

Acute toxicity:

oral GHS: out of Category.

skin Unknown.

inhalation (gas) GHS: exempt from a classification.

inhalation (steam) Unknown.

inhalation (mist) GHS: It is not possible to classify it due to data deficiency.

- Skin corrosivity: Unknown.
- Serious damage and irritant property for eyes: Unknown.
- Respiratory or skin sensitization:

Respiratory sensitization: GHS: Category 1

The allergy, asthma or breathing difficulties might be caused when inhaling.

Skin sensitization: GHS: Category 1

The allergic skin reaction might be caused.

- · Germline mutagenicity: Unknown.
- · Carcinogenicity:

GHS: Category 2

ACGIH: A3 -Confirmed animal carcinogen but relevance to human carcinogen is unknown.

IARC: Group 2B Possibly carcinogenic to human. The cancer might be caused.

Reproduction Toxicity :

GHS: Category 2.

The adverse effect on reproductive competence or the fetus might occur.



Product name: Cylindrical Nickel - Metal Hydride Battery

Certain target organ/ Systemic toxicity (single exposure):
 GHS: Category 3(respiratory tract irritating properties).
 The respiratory organ might be stimulated.

Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1(respiratory organ).

The disorder of the respiratory organ is caused by long-term or repeated exposure.

Manganese compounds

Acute toxicity:

oral

GHS: out of Category.

skin

Unknown.

inhalation (gas)

GHS: exempt from a classification.

inhalation (steam mist)

Unknown.

- Skin corrosivity: GHS: Category 3. Slight skin stimulation.
- Serious damage and irritant property for eyes: GHS: Category 2B. eye stimulation.
- · Respiratory or skin sensitization:

Respiratory sensitization: Unknown.

Skin sensitization: Unknown.

- Germline mutagenicity: GHS: It is not possible to classify.
- Carcinogenicity: GHS: out of Category.
- Reproduction Toxicity: GHS: Category 1B.

The adverse effect on reproductive competence or the fetus might occur.

Certain target organ/ Systemic toxicity (single exposure):

GHS: Category 1(respiratory organ).

The disorder of the respiratory organ is caused.

Certain target organ/ Systemic toxicity (repeated exposure);

GHS: Category 1(respiratory organ, nerve).

The disorder of the respiratory organ and nerve system is caused by long-term or repeated inhalation exposure.

Aluminum Compounds

Acute toxicity:

oral, skin, inhalation(steam, dust) Unknown.

- Skin corrosivity: Unknown.
- Serious damage and irritant property for eyes: Unknown.
- Respiratory or skin sensitization:

Respiratory sensitization: Unknown.

Skin sensitization: Unknown.

- Germline mutagenicity: Unknown.
- Carcinogenicity: Unknown.
- · Reproduction Toxicity: Unknown.
- Certain target organ/ Systemic toxicity (single exposure): Unknown.
- Certain target organ/ Systemic toxicity (repeated exposure);

GHS: Category 1 and 2.

The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.(Category 1)



Product name: Cylindrical Nickel –Metal Hydride Battery

The disorder of the nerve system by long-term or repeated oral exposure might be caused. (Category 2) The disorder of the nerve system by long-term or repeated oral exposure might be caused.

Zinc oxide

Acute toxicity:

oral rat LD50 > 5000mg/kg

inhalation (dust, mist) rat LC50 > 5.7mg/l The harmful might be caused when inhaling.

- · Skin corrosivity: GHS: out of Category.
- Serious damage and irritant property for eyes: GHS: out of Category
- · Respiratory or skin sensitization:

Respiratory sensitization: Unknown.

Skin sensitization: GHS: out of Category.

- Germline mutagenicity: Unknown.
- Carcinogenicity: GHS: out of Category.
- Reproduction Toxicity: GHS: out of Category.
- Certain target organ/ Systemic toxicity (single exposure):

GHS: Category 1.

The disorder of the whole body

Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1.

The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.

Carbon Black

Acute toxicity:

oral rat LDso >15400 mg/kg

skin Unknown.

inhalation (dust) Unknown.

- Skin corrosivity: Unknown.
- Serious damage and irritant property for eyes: Unknown.
- · Respiratory or skin sensitization:

Respiratory sensitization: Unknown.

Skin sensitization: Unknown.

- Germline mutagenicity: Unknown.
- · Carcinogenicity:

GHS: Category 2

ACGIH: A3 -Confirmed animal carcinogen but relevance to human carcinogen is unknown.

IARC: Group 2B Possibly carcinogenic to human.

The cancer might be caused.

- Reproduction Toxicity: Unknown.
- Certain target organ/ Systemic toxicity (single exposure): Unknown.
- Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1

The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.



Product name: Cylindrical Nickel –Metal Hydride Battery

Potassium Hydroxide

Acute toxicity:

oral GHS: Category 3. Harmful if swallowed.

skin GHS: It is not possible to classify.

I nhalation (steam) GHS: It is not possible to classify.

inhalation (dust) GHS: It is not possible to classify.

Skin corrosivity: GHS: Category 1B.

Serious chemical wound of the skin and damage of eyes is caused.

- · Serious damage and irritant property for eyes: GHS: Category 1.
- Respiratory or skin sensitization:

Respiratory sensitization: GHS: It is not possible to classify.

Skin sensitization: GHS: out of Category.

- Germline mutagenicity: GHS: out of Category.
- Carcinogenicity: GHS: It is not possible to classify.
- Reproduction Toxicity: GHS: It is not possible to classify.
- Certain target organ/ Systemic toxicity (single exposure):

GHS: Category 1.

The disorder of the respiratory system is caused.

• Certain target organ/ Systemic toxicity (repeated exposure)

GHS: It is not possible to classify.

Sodium Hydroxide

Acute toxicity:

oral GHS: It is not possible to classify.

skin GHS: It is not possible to classify.

inhalation (gas) GHS: out of Category.

inhalation (steam) Unknown.

inhalation (dust) Unknown.

· Skin corrosivity: GHS: Category 1.

Serious chemical wound of the skin and damage of eyes is caused.

- Serious damage and irritant property for eyes: GHS: Category 1. Serious damage of eyes is caused.
- Respiratory or skin sensitization:

Respiratory sensitization: GHS: It is not possible to classify.

Skin sensitization: GHS: out of Category.

- · Germline mutagenicity : GHS: out of Category
- Carcinogenicity: GHS: It is not possible to classify.
- Reproduction Toxicity: GHS: It is not possible to classify.
- Certain target organ/ Systemic toxicity (single exposure):

GHS: Category 1(respiratory system).

The disorder of the respiratory organ is caused.

• Certain target organ/ Systemic toxicity (repeated exposure):

GHS: It is not possible to classify.



Product name: Cylindrical Nickel -Metal Hydride Battery

Lithium Hydroxide

Acute toxicity:

oral GHS: Category 3. Harmful if swallowed.

skin Unknown.

inhalation (steam) Unknown.

inhalation (dust) GHS: Category 3. Harmful if inhaled.

Skin corrosivity : GHS: Category 1.

Serious chemical wound of the skin and damage of eyes is caused.

- Serious damage and irritant property for eyes: GHS: Category 1.
- · Respiratory or skin sensitization:

Respiratory sensitization: GHS: It is not possible to classify.

Skin sensitization: GHS: It is not possible to classify.

- · Germline mutagenicity: Unknown.
- Carcinogenicity: Unknown.
- Reproduction Toxicity: Unknown.
- Certain target organ/ Systemic toxicity (single exposure):

GHS: Category 1.

The disorder of the respiratory system is caused by inhalation exposure.

Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1&2.

The disorder of the respiratory system is caused by long-term or repeated inhalation exposure. The disorder of the liver and the hematopoietic system by long-term or repeated oral exposure might be caused.

12. ECOLOGICAL INFORMATION

Persistence/degradability:

Since a battery and the internal cell materials remain in the environment, do not bury or dispose into the environment.

13. DISPOSAL CONSIDERATION

• Recommended methods for safe and environmentally preferred disposal:

Product (waste from residues)

Do not dispose into the waste stream. Recycle through an authorized recycling company.



Product name: Cylindrical Nickel – Metal Hydride Battery
Contaminated packaging

Neither a container nor packaging is contaminated during normal use. When internal materials leaked from a battery cell contaminates the container, dispose as industrial waste, subject to special control.

14.TRANSPORT INFORMATION

This battery does not require the following items.

- TECHNICAL INSTRUCTIONS FOR THE SAFE TRANSPORT OF DANGEROUS GOODS BY AIR(ICAO)
- IATA Dangerous Goods Regulations(IATA)
- code of federal regulations (U.S.DOT)
 This battery requires the following items.
- INTERNATIONAL MARITIME DANGEROUS GOODS CODE(IMO)
 From the 1st January 2012, Nickel-Metal Hydride Batteries is classed as Dangerous Goods,

Class 9 inaccordance with United Nations Recommendations on the Transport of Dangerous Goods and will have the following UN Number:

UN No. Proper Shipping Class or division Packing Group Special Provisions

3496 BATTERIES, NICKEL-METAL HYDRIDE

Class or division Packing Group Special Provisions

- 117
963

Instructions and contents of Special Provisions (117 and 963) for this UN number include:

- Specifying it is only regulated when transported by sea,
- Ni-MH button cells are not subject to the provisions of this code.
- Ni-MH cells or batteries packed with or contained in equipment are not subject to the provisions of this code.
- All other Ni-MH cells or batteries shall be securely packed and protected from short circuit.
 They are not

subject to other provisions of this code provided they are loaded in a cargo transport unit in a total quantity of less than 100 Kg gross mass. When loaded in a cargo transport unit in a total quantity of 100 Kg gross mass or more, only subject to:

- Provided dangerous goods transportation information by a) Consignor and b) Shipper.
- Stowage and segregation provisions: as prescribed in Chapter 3 of IMDG Code: "away from" sources

of heat as minimum horizontal separation of 3 metres.

Prior to transportation, confirmation that there is no leakage and no spillage from a container is necessary. Cargo must be handle without falling, dropping or breakage. Care must be taken to prevent the collapse of cargo piles or saturation by rain. Containers must be handled carefully. Packaging is constructed to prevent short-circuiting and/or electric shock. The product is handled as Non-Dangerous Goods by based on IATA(A123) for air shipment.



Product name: Cylindrical Nickel – Metal Hydride Battery
15. REGULATORY INFORMATION

Regulations specifically applicable to the product:
 Wastes Management and Public Cleaning Law (Japan)
 Law for Promotion Effective Utilization of Resources (Japan)
 Commission Directive 2006/66/EU (EU)

OTHER INFORMATION

- The information contained in this safety data sheet is based on the present state of knowledge and current legislation.
- The safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Reference

Chemical substances information: Japan Advanced Information center of Safety and Health International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Center (CIS)
2011 TLVs and BEIs: American Conference of Governmental Industrial Hygienists (ACGIH)
NIOSH CARCINOGEN LIST: National Institute for Occupational Safety and Health (NIOSH)
The Ninth Report on Carcinogen: National Toxicology Program (NTP)
IARC Monographs Program on the Evaluation of Carcinogenic Risks to Humans:
International Agency for Research on Cancer (IARC)

Globally Harmonized System of Classification and Labelling of Chemicals(GHS) National Institute of Technology and Evaluation(NITE)